

Lorient LVH-44

Intumescent Square/Rectangular Fire Dampers

Use

- o Square/rectangular intumescent fire damper for walls, floors and ceilings



Features

- o Integrity Fire Rating – up to 4 hours
- o Damper Depth 44 mm
- o Sizes available from 45 mm to over 10,000 mm
- o Innovative, slimline design
- o Simple installation
- o Suitable for retrofit of seized mechanical dampers
- o Approvals for wall, floor and ceiling mounting
- o No thermal expansion clearances during installation
- o Reduced maintenance and resultant cost saving

Ordering Information

Product Code	Size
LVH44-100/100	100 mm×100 mm
LVH44-100/125	100 mm×125 mm
LVH44-125/125	125 mm×125 mm
LVH44-125/150	125 mm×150 mm
LVH44-150/150	150 mm×150 mm
LVH44-150/175	150 mm×175 mm
LVH44-175/175	175 mm×175 mm
LVH44-175/200	175 mm×200 mm
LVH44-200/200	200 mm×200 mm
LVH44-200/250	200 mm×250 mm
LVH44-250/250	250 mm×250 mm
LVH44-250/300	250 mm×300 mm
LVH44-300/300	300 mm×300 mm
LVH44-300/350	300 mm×350 mm
LVH44-350/350	350 mm×350 mm
LVH44-350/400	350 mm×400 mm
LVH44-400/400	400 mm×400 mm
LVH44-400/450	400 mm×450 mm
LVH44-450/450	450 mm×450 mm
LVH44-450/500	450 mm×500 mm
LVH44-500/500	500 mm×500 mm
LVH44-500/550	500 mm×550 mm
LVH44-550/550	550 mm×550 mm
LVH44-550/600	550 mm×600 mm
LVH44-600/600	600 mm×600 mm

Customised sizes are available up to 10 m×10 m

Accessories

FIRE RATED MASTIC

- o Grey fire mastic seal to be used with all fire intumescent fire dampers

Product Code	Weight
LVHFRMG	310 g